

S-SERIES SPECIFICATIONS

Model	S200	S300
Electrical:		
Voltage, Single Phase	220	220
Hertz	50 / 60	50 / 60
Amps - max draw	28 amp	36 amp
Cord Plug Rating (UL Listed)	30 amp	50 amp
Brew & Steam Specifications:		
Watts per Element, Steam Tank	2000 x 2	2500 x 2
Total Steam Element Wattage	4000	5000
Steam Tank Capacity (Liters)	7.7	12.3
Watts per Element, Brew Tank	700 x 2	700 x 3
Brew Tank Capacities (Liters)	1.9 x 2	1.9 x 3
Machine Dimensions:		
	Inches / mm	Inches / mm
Height	16.9" / 428	16.9" / 428
Width	27.6" / 702	37" / 940
Depth	24" / 610	24" / 610
Weights & Dimensions:		
	Lbs / Kgs	Lbs / Kgs
Machine Weight, Empty	152 / 69	225 / 102
Shipping Weight (approximate)	252 / 114	332 / 151
Boxed Dimensions: L" x W" x H"	33" x 36" x 30"	33" x 46" x 30"
Boxed Dimensions: L x W x H (mm)	838x914x762	838x1168x762
Plumbing (Compression):		
	3/8" OD	3/8" OD

- Certified by ETL for Sanitation to NSF / ANSI Standard 4
- Certified by ETL for Electrical Safety to ANSI / UL Standard 197
- Certified by ETL for Electrical Safety to CSA Standard C22.2 No. 109
- Certified by KTL for Korean Licensing Standards
- CE Compliant (By request)
- C-Tick Compliant (By request)

