

## SOFTENERS











## Softeners



2019--0539

## MWG Manual Water Softeners

- Suitable for residential and commercial water softening applications, as coffee machines, dishwashers, microwave ovens;
- Tank in 304 Stainless Steel;
  They work with mains water pressure;
- They are supplied with and must be operated only with resin approved for drinking water contact use;
- For regeneration use only Sodium Chloride (NaCl) = coarse cooking salt;
   All the constituent materials comply with the requirements of Italian Ministerial Decree 174 dated 04-04-2004, materials in contact with drinking water.

## **Technical characteristics:**

- Nominal Flow Rate at 4 bar = 1.000 l/h
- Nominial Flow Rate at 4 bar = 1.000 /m
  Operating Water Pressure Range: 1 ÷ 4 bar
  Feed Water Temperature Range: 4 ÷ 25°C
  Room Temperature Range: 4 ÷ 35° C
  Connections: 3/4" G 3/8" G

Ref	Description	Fam.	Subfa m.	Disp. Stock	
ADD06	MWG MANUAL WATER SOFTENER 6 L	405	805	•	
ADD08	MWG MANUAL WATER SOFTENER 8 L	405	805	•	
ADD12	MWG MANUAL WATER SOFTENER 12 L	405	805	•	
ADD16	MWG MANUAL WATER SOFTENER 16 L	405	805	•	
ADD20	MWG MANUAL WATER SOFTENER 20 L	405	805	•	

Ref	Box: WxLxH.	Box: Q.ty	Box: Weight.	Pallet: WxLxH.	Pallet: Q.ty	Pallet: Weight.
ADD06						
ADD08						
ADD12						
ADD16						
ADD20						

Certificates	Manufacturer	Sectors
DM174-2004	MWG	Domestic, Commercial

