

#### MMD-AP0276BH-E Standard Ducted Indoor Unit

- External static pressure can be raised up to 120 Pa
- Low noise: low fan speed down to 26dB(A)
- Fresh air intake
- Lift pump up to 850mm lift
- Ideal for restricted ceiling voids only 275mm high
- Base or Rear return air

Model Reference	MMD-0276BH-E
Nominal Cooling (kW)	8.0
Nominal Heating (kW)	9.0
Capacity Code	3.0
Power Input (Cool/Heat) (kW)	0.077
UK Cooling (kW)	7.3
UK Sensible Cooling (kW)	5.5
UK Heating (kW)	7.38
Starting Current (A)	0.90
Running Current (A)	0.52
Suggested Fuse Size (A)	3
Power Supply (V-ph-Hz)	220/240-1-50
Interconnecting Cable	2 Core Screened 1.5mm
Sound Power H-M-L (dB(A))	46-44-42
Sound Pressure H-L (dB(A))	36-27
Air Flow H-L (m <sup>3</sup> /h)	1200-720
External Static Pressure (Factory Default) Pa	40
Static Pressure Range Pa	30—120 (7 steps)
Dimension (HxWxD) mm	275 x 1000 x 750
Weight (kg)	30

All duties are connected capacity and do not take in to account any de-rate for pipe lengths etc.  
 UK Cooling Conditions Int. -23°C DB/16°C WB Ext 29°C DB  
 UK Heating Conditions Int. -21°C DB Ext -5°C WB

