

MVP HYDRA SPECIFICATIONS

<u>Model</u>	<u>1 Group</u>	<u>2 Group</u>	<u>3 Group</u>
Electrical:			
Voltage, Single Phase	220	220	220
Hertz	50 / 60	50 / 60	50 / 60
Amps - max draw	16 amp	30 amp	40 amp
Cord Plug Rating (UL Listed)	20 amp	30 amp	50 amp
Brew & Steam Specifications:			
Watts per Element, Steam Tank	1000 x 2	2000 x 2	2500 x 2
Total Steam Element Wattage	2000	4000	5000
Steam Tank Capacity (Liters)	3.2	7.7	12.3
Watts per Element, Brew Tank	700	700 x 2	700 x 3
Brew Tank Capacities (Liters)	1.9	1.9 x 2	1.9 x 3
Machine Dimensions:			
	Inches / mm	Inches / mm	Inches / mm
Height	21" / 534	21" / 534	21" / 534
Width	19" / 483	30" / 762	41" / 1042
Depth	24" / 610	24" / 610	24" / 610
Weights & Dimensions:			
	Lbs / Kgs	Lbs / Kgs	Lbs / Kgs
Machine Weight, Empty	106 / 48	154 / 70	190 / 86
Shipping Weight (approximate)	190 / 86	260 / 118	324 / 147
Boxed Dimensions: L" x W" x H"	42" x 30" x 31"	42" x 32" x 31"	50" x 32" x 31"
Boxed Dimensions: L x W x H (mm)	1042 x 762 x 787	1042 x 762 x 787	1245 x 813 x 787
Plumbing (Compression):			
	3/8" OD	3/8" OD	3/8" OD

- Certified by ETL for Sanitation to NSF / ANSI Standard 4
- Certified by ETL for Electrical Safety to ANSI / UL Standard 197
- Certified by ETL for Electrical Safety to CSA Standard C22.2 No. 109
- Certified by KTL for Korean Licensing Standards
- CE Compliant (By request)
- C-Tick Compliant (By request)

