

Isetta

Promotional ice-cream cabinets with static refrigeration, finned evaporator and automatic electric defrosting. One piece body with ecological polyurethane insulation (HCFC & HFC free), foamed with CO₂. Internal and external tank in plastified sheet. This cabinet can be fitted with a double level of ice-cream containers H120 and it is equipped with a storage cell with internal foamed evaporator (except for the model ISETTA 4). Tempered glass structure, available in two versions, ST (straight front glass) or LX (curved front glass). Rear pivoting methacrylate panel system on operator side. Work top in plastified sheet with internal led lighting. Built-in hermetic condensing unit with electronic control board. Available in Special Performance TP model working in class 7, 35°C, 75 RH. Main structure in carbon steel painted with powder, 4 pivoting wheels for an easier handling.

Vetrine gelato promozionali a refrigerazione statica con evaporatore alettato e sbrinamento automatico elettrico. Scocca monolitica coibentata con poliuretano ecologico (HCFC & HFC free) espanso a CO₂. Interno ed esterno vasca in lamiera preverniciata. La vetrina può contenere un doppio livello di vaschette H120 ed è dotata di cella di riserva a refrigerazione statica con evaporatore a mantello [eccetto il modello ISETTA 4]. Sovrastruttura in vetro temperato, disponibile nelle due versioni, ST (vetro frontale dritto) o LX (vetro frontale curvo). Chiusura lato operatore tramite ribaltina basculante in metacrilato. Piano di lavoro in lamiera plastificata, con plafoniera di illuminazione con led sul lato interno vasca. Unità condensatrice ermetica a bordo con quadro comandi elettronico. Versione TP tropicalizzata [classe 7, 35°C; 75% UR]. Struttura in acciaio al carbonio verniciato a polvere, con 4 ruote pivotanti per facilitarne la movimentazione.



ENERGY SAVING
Led



INSTALLATION
Plug-in



TEMPERATURE
-16/-14 °C



DEFROST
Electric



CLIMATIC CLASS
7





Isetta Catalog - Catalogo

Model Modello		Code Codice			Condensing unit included Unità condensatrice a bordo	
		R404A	R290		R404A Air / Aria	R290 Air / Aria
RS	ST TP	4	9001023000401	-	*****	*****
		6R	9001023000601	-	*****	-
		7R	9001023000701	-	*****	*****
RS	LX TP	4	9001023100401	-	*****	*****
		6R	9001023100601	-	*****	-
		7R	9001023100701	-	*****	*****
		9R	9001023100901	-	*****	-
		12R	9001023101201	-	*****	-

Isetta Technical features - Caratteristiche tecniche

	4	6R	7R
External dimensions [LxDxH] Dimensioni esterne [LxPxH]	824 x 760 x 1176 mm	1184 x 800 x 1176 mm	1354 x 800 x 1176 mm
Storage containers capacity Capacità vaschette di riserva	-	4 [+4] / 5 lt - 6 / 4,75 lt	6 [+6] / 5 lt - 8 / 4,75 lt
Net weight Peso netto	69 kg	97 kg	102 kg
Refrigeration Refrigerazione	Static - Statica		
Refrigerant Refrigerante	R404A ^[1] - R290 ^[2]		
Climatic class Classe climatica	7		
Operating conditions Condizioni ambientali	35 °C / 75 %RH		
Product temperature Temperatura prodotto	-16/-14 °C		
Compressor [q.ty-type] Compressore [q.tà-tipologia]	1 Hermetic - 1 Ermetico		
Defrost Sbrinamento	Electrical - Elettrico		
Power supply Alimentazione	230 V / 1 Ph / 50 Hz		
Electrical input [standard] Assorbimento elettrico [standard]	^[1] 330 W / 2,3 A	^[2] 300 W / 2,4 A	^[1] 590 W / 4,1 A
Electrical input [defrost] Assorbimento elettrico [sbrinamento]	^[1] 810 W / 3,8 A	^[2] 810 W / 3,8 A	^[1] 810 W / 3,7 A

Stainless steel containers

Vaschette inox


Piled up double row
 Doppia fila di riserva

5 Lt

 360 x 165 x 120h
 9001990000005
 ***** each/cad.

4,75 Lt





 260 x 157 x 170h
 9001990000003
 ***** each/cad.

4+[4]	6	+Support Kit container - kit distanziali *** 9001090930400
6+[6]	10	+Support Kit container - kit distanziali *** 9001090930600
7+[7]	11	+Support Kit container - kit distanziali *** 9001090930700

4+[4]	6	+Support Kit container - kit distanziali *** 9001090930400
6+[6]	10	+Support Kit container - kit distanziali *** 9001090930600
7+[7]	11	+Support Kit container - kit distanziali *** 9001090930700
9+[9]	14	+Support Kit container - kit distanziali *** 9001090930900
12+[12]	19	+Support Kit container - kit distanziali *** 9001090931200

Section - Sezioni

9R	12R
1659 x 800 x 1176 mm	2119 x 800 x 1176 mm
7 [+7] / 5 lt - 10 / 4,75 lt	10 [+10] / 5 lt - 14 / 4,75 lt
160 kg	217 kg
Static - Statica	
R404A [1] - R290 [2]	
7	
35 °C / 75 %RH	
-16/-14 °C	
1 Hermetic - 1 Ermetico	2 Hermetic - 2 Ermetico
Electrical - Elettrico	
230 V / 1 Ph / 50 Hz	
[1] 930 W / 5,5 A	[1] 1045 W / 5,6 A
[1] 1330 W / 5,8 A	[1] 1755 W / 8,2 A

ST 4

ST 6R-7R

LX 4

LX 6R-7R-9R-12R


Isetta **Optionals** - Elementi opzionali

Item	Accessorio	Mod.	Code	Price
White cone holder	Portaconi completo bianco	-	9001390900700	*****
Scoop washer with stainless steel container	Lavaporzionate vaschetta inox	-	9001920000262	*****
Front sticker PM_AD1	Adesivo Frontale PM_AD1	4	9001091000006	*****
		6R	9001091000005	*****
		7R	9001091000003	*****
		9R	9001091000004	*****
		12R	9001091000007	*****



PM_AD1

Isetta **Customizable area** - Aree personalizzabili

